

# The Greedy Dirichlet Process Filter

## An Online Clustering Multi-Target Tracker

**Benjamin Naujoks**, Patrick Burger and Hans-Joachim Wuensche

University of the Bundeswehr Munich  
Department for Aerospace Engineering  
Institute for Autonomous Systems Technology

2018-11-27



- 1 Motivation / Problem Description
- 2 Temporally-Dependent Dirichlet Process Mixture Model
- 3 Greedy Dirichlet Process Filter
- 4 Evaluation & Results
- 5 Summary





- 1 Motivation / Problem Description
- 2 Temporally-Dependent Dirichlet Process Mixture Model
- 3 Greedy Dirichlet Process Filter
- 4 Evaluation & Results
- 5 Summary





## Problem Description

- Goal:
  - Estimate dynamics and dimensions of an unknown number of targets in real-time
  - Associate measurements to correct target
- Challenges:
  - Multiple measurements of one target
  - Unknown number of targets



## Problem Description

- Goal:
  - Estimate dynamics and dimensions of an unknown number of targets in real-time
  - Associate measurements to correct target
- Challenges:
  - Multiple measurements of one target
  - Unknown number of targets



- 1 Motivation / Problem Description
- 2 Temporally-Dependent Dirichlet Process Mixture Model**
- 3 Greedy Dirichlet Process Filter
- 4 Evaluation & Results
- 5 Summary



## Dirichlet Process

- Bayesian non-parametric model
- It is a distribution over distributions with an infinite amount of mixture components
- Only finite ones are activated by observations
- Defined by a concentration parameter  $\alpha \in \mathbb{R}$  and random mixing measure  $G_0$



## Dirichlet Process

- Bayesian non-parametric model
- It is a distribution over distributions with an infinite amount of mixture components
- Only finite ones are activated by observations
- Defined by a concentration parameter  $\alpha \in \mathbb{R}$  and random mixing measure  $G_0$



## Dirichlet Process

- Bayesian non-parametric model
- It is a distribution over distributions with an infinite amount of mixture components
- Only finite ones are activated by observations
- Defined by a concentration parameter  $\alpha \in \mathbb{R}$  and random mixing measure  $G_0$



## Dirichlet Process

- Bayesian non-parametric model
- It is a distribution over distributions with an infinite amount of mixture components
- Only finite ones are activated by observations
- Defined by a concentration parameter  $\alpha \in \mathbb{R}$  and random mixing measure  $G_0$



## Chinese Restaurant Process

- Realization of a DP
  - Either: new customer (measurement) chooses new table (component) proportional to  $\alpha$
  - Or: joins known table with probability proportional to the number of occupying customers
- ⇒ Conditional prior, with  $n_k(t)$  – the number of assigned measurements to cluster  $k$  [1]:

$$CRP(\alpha) = \begin{cases} \frac{n_k(t)}{i-1+\alpha} & k \in K_t, \\ \frac{\alpha}{i-1+\alpha} & \text{else} \end{cases} . \quad (1)$$



## Chinese Restaurant Process

- Realization of a DP
  - Either: new customer (measurement) chooses new table (component) proportional to  $\alpha$
  - Or: joins known table with probability proportional to the number of occupying customers
- ⇒ Conditional prior, with  $n_k(t)$  – the number of assigned measurements to cluster  $k$  [1]:

$$CRP(\alpha) = \begin{cases} \frac{n_k(t)}{i-1+\alpha} & k \in K_t, \\ \frac{\alpha}{i-1+\alpha} & \text{else} \end{cases} . \quad (1)$$



## Chinese Restaurant Process

- Realization of a DP
- Either: new customer (measurement) chooses new table (component) proportional to  $\alpha$
- Or: joins known table with probability proportional to the number of occupying customers

⇒ Conditional prior, with  $n_k(t)$  – the number of assigned measurements to cluster  $k$  [1]:

$$CRP(\alpha) = \begin{cases} \frac{n_k(t)}{i-1+\alpha} & k \in K_t, \\ \frac{\alpha}{i-1+\alpha} & \text{else} \end{cases} . \quad (1)$$



## Chinese Restaurant Process


- Realization of a DP
  - Either: new customer (measurement) chooses new table (component) proportional to  $\alpha$
  - Or: joins known table with probability proportional to the number of occupying customers
- ⇒ Conditional prior, with  $n_k(t)$  – the number of assigned measurements to cluster  $k$  [1]:

$$CRP(\alpha) = \begin{cases} \frac{n_k(t)}{i-1+\alpha} & k \in K_t, \\ \frac{\alpha}{i-1+\alpha} & \text{else} \end{cases} . \quad (1)$$



## Example of CRP

- $CRP(\alpha)$  for assignment of customer  $C_5$  with  $\alpha = 0.1$ :
  - Table 1:  $\frac{3}{5-1+0.1} = \mathbf{0.73}$
  - Table 2:  $\frac{1}{5-1+0.1} = 0.24$
  - New Table:  $\frac{0.1}{5-1+0.1} = 0.024$



## Distance-Dependent CRP I

- Links customers to customers rather than tables
- Conditional prior, with link assignment  $j_i(t)$  and set of previous assignments  $j_i$  [2]:

$$p(j_i(t) = l | \mathbf{j}_{-i}, \alpha) = \begin{cases} d_{il}(\mathbf{y}_i(t), \mathbf{y}_l(t)) & i \neq l, \\ \alpha & i = l \end{cases}, \quad (2)$$




## Distance-Dependent CRP I

- Links customers to customers rather than tables
- Conditional prior, with link assignment  $j_i(t)$  and set of previous assignments  $\mathbf{j}_i$  [2]:

$$p(j_i(t) = l | \mathbf{j}_{-i}, \alpha) = \begin{cases} d_{il}(\mathbf{y}_i(t), \mathbf{y}_l(t)) & i \neq l, \\ \alpha & i = l \end{cases}, \quad (2)$$



## Distance-Dependent CRP II



## Grid Example for Distance-Dependent CRP

		?			
	1	1	?		
	1	1			





## Data to Cluster Assignment

- Can be interpreted as a cluster prior dependent on the current cluster parameters
- Measurement  $\mathbf{y}_i(t)$  to cluster  $k$  assignment [1]:

$$\begin{aligned}\pi_{z_i(t)=k} &= p(z_i(t) = k | \mathbf{z}(t-1), \mathbf{y}_i(t)) \\ &= p(\mathbf{y}_i(t) | \boldsymbol{\theta}_k(t)) \cdot p(z_i(t) = k | \mathbf{z}(t-1)),\end{aligned}\tag{3}$$



# Cluster Prior Examples



## Kalman Filtering

- Kalman Filtering is used for the dynamical part  $\mathbf{x} \in \mathbb{R}^n$  of the mixture components
- Probabilistic Gaussian state space model, with transition matrix  $\Phi(t-1) \in \mathbb{R}^{n \times n}$ , measurement model matrix  $\mathbf{C}(t) \in \mathbb{R}^{m \times n}$ , unbiased and Gaussian process noise  $\mathbf{Q}(t-1)$  and Gaussian measurement noise  $\mathbf{R}(t)$  [3]:

$$p(\mathbf{x}(t)|\mathbf{x}(t-1)) = \mathcal{N}(\mathbf{x}(t)|\Phi(t-1)\mathbf{x}(t-1), \mathbf{Q}(t-1)) \quad (4)$$

$$p(\mathbf{y}(t)|\mathbf{x}(t)) = \mathcal{N}(\mathbf{y}(t)|\mathbf{C}(t)\mathbf{x}(t), \mathbf{R}(t)), \quad (5)$$



## Kalman Filtering

- Kalman Filtering is used for the dynamical part  $\mathbf{x} \in \mathbb{R}^n$  of the mixture components
- Probabilistic Gaussian state space model, with transition matrix  $\Phi(t-1) \in \mathbb{R}^{n \times n}$ , measurement model matrix  $\mathbf{C}(t) \in \mathbb{R}^{m \times n}$ , unbiased and Gaussian process noise  $\mathbf{Q}(t-1)$  and Gaussian measurement noise  $\mathbf{R}(t)$  [3]:

$$p(\mathbf{x}(t)|\mathbf{x}(t-1)) = \mathcal{N}(\mathbf{x}(t)|\Phi(t-1)\mathbf{x}(t-1), \mathbf{Q}(t-1)) \quad (4)$$

$$p(\mathbf{y}(t)|\mathbf{x}(t)) = \mathcal{N}(\mathbf{y}(t)|\mathbf{C}(t)\mathbf{x}(t), \mathbf{R}(t)), \quad (5)$$



- 1 Motivation / Problem Description
- 2 Temporally-Dependent Dirichlet Process Mixture Model
- 3 Greedy Dirichlet Process Filter**
- 4 Evaluation & Results
- 5 Summary



## Basic Procedure

Greedy Dirichlet Process Filter (GDPF) consists of the following two main steps:

- Choosing best label for measurement  $y_i$
- Update posterior distribution



## Choosing the Best Label

- Conditional posterior probability of assigning measurement  $\mathbf{y}_i(t)$  to cluster  $k$  given previous data for measurements  $\mathbf{Y}^i(t)$  is a combination of distance-dependent CRP and data to cluster assignment
- Conditional posterior probabilities [1]:

$$p\left(z_i(t) = k \mid \mathbf{Y}^i(t), \mathbf{j}_{-i}, \mathbf{z}(t-1)\right) = \frac{p(j_i = l_k \mid \mathbf{j}_{-i}, \alpha) \cdot \pi_{z_i(t)=k}}{\sum_{m \in K_t} p(j_i = l_m \mid \mathbf{j}_{-i}, \alpha) \cdot \pi_{z_i(t)=m}}. \quad (6)$$



## Choosing the Best Label

- Conditional posterior probability of assigning measurement  $\mathbf{y}_i(t)$  to cluster  $k$  given previous data for measurements  $\mathbf{Y}^i(t)$  is a combination of distance-dependent CRP and data to cluster assignment
- Conditional posterior probabilities [1]:

$$p\left(z_i(t) = k \mid \mathbf{Y}^i(t), \mathbf{j}_{-i}, \mathbf{z}(t-1)\right) = \frac{p(j_i = l_k \mid \mathbf{j}_{-i}, \alpha) \cdot \pi_{z_i(t)=k}}{\sum_{m \in K_t} p(j_i = l_m \mid \mathbf{j}_{-i}, \alpha) \cdot \pi_{z_i(t)=m}}. \quad (6)$$



## Posterior Update

- Posterior distribution of cluster parameters consists of:
  - Generation of new components:  $G_0(\theta_{z_i(t)=k}(t))$
  - Dynamical part:  $p(\mathbf{y}_i(t)|\theta_{z_i(t)=k}(t))$
  - Time evolution of cluster parameters:  $p(\theta_{z_i(t)=k}(t)|\theta_{z_i(t-1)=k}(t-1))$
- It follows [1]:

$$\begin{aligned}
 p(\theta_{z_i(t)}|\mathbf{y}_{i-1}(t), \mathbf{z}(t)) &\propto G_0(\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\mathbf{y}_i(t)|\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\theta_{z_i(t)=k}(t)|\theta_{z_i(t-1)=k}(t-1)), \tag{7}
 \end{aligned}$$



## Posterior Update

- Posterior distribution of cluster parameters consists of:
  - Generation of new components:  $G_0(\theta_{z_i(t)=k}(t))$
  - Dynamical part:  $p(\mathbf{y}_i(t)|\theta_{z_i(t)=k}(t))$
  - Time evolution of cluster parameters:  $p(\theta_{z_i(t)=k}(t)|\theta_{z_i(t-1)=k}(t-1))$
- It follows [1]:

$$\begin{aligned}
 p(\theta_{z_i(t)}|\mathbf{y}_{i-1}(t), \mathbf{z}(t)) &\propto G_0(\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\mathbf{y}_i(t)|\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\theta_{z_i(t)=k}(t)|\theta_{z_i(t-1)=k}(t-1)), \tag{7}
 \end{aligned}$$



## Posterior Update

- Posterior distribution of cluster parameters consists of:
  - Generation of new components:  $G_0(\theta_{z_i(t)=k}(t))$
  - Dynamical part:  $p(\mathbf{y}_i(t)|\theta_{z_i(t)=k}(t))$
  - Time evolution of cluster parameters:  $p(\theta_{z_i(t)=k}(t)|\theta_{z_i(t-1)=k}(t-1))$
- It follows [1]:

$$\begin{aligned}
 p(\theta_{z_i(t)}|\mathbf{y}_{i-1}(t), \mathbf{z}(t)) &\propto G_0(\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\mathbf{y}_i(t)|\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\theta_{z_i(t)=k}(t)|\theta_{z_i(t-1)=k}(t-1)), \tag{7}
 \end{aligned}$$



## Posterior Update

- Posterior distribution of cluster parameters consists of:
  - Generation of new components:  $G_0(\theta_{z_i(t)=k}(t))$
  - Dynamical part:  $p(\mathbf{y}_i(t) | \theta_{z_i(t)=k}(t))$
  - Time evolution of cluster parameters:  $p(\theta_{z_i(t)=k}(t) | \theta_{z_i(t-1)=k}(t-1))$
- It follows [1]:

$$\begin{aligned}
 p(\theta_{z_i(t)} | \mathbf{y}_{i-1}(t), \mathbf{z}(t)) &\propto G_0(\theta_{z_i(t)=k}(t)) \\
 &\cdot p(\mathbf{y}_i(t) | \theta_{z_i(t)=k}(t)) \\
 &\cdot p(\theta_{z_i(t)=k}(t) | \theta_{z_i(t-1)=k}(t-1)), \tag{7}
 \end{aligned}$$



- 1 Motivation / Problem Description
- 2 Temporally-Dependent Dirichlet Process Mixture Model
- 3 Greedy Dirichlet Process Filter
- 4 Evaluation & Results**
- 5 Summary



## Test Scenario

- Real-world scenario in the suburbs near our university
- Passing cars as dynamic objects
- Ground truth obtained with an installed INS-sensor
- Goal: Estimate x- and y-position of our ground-truth object without id-switches
- Tested against:
  - Labeled Multi-Bernoulli Filter (LMB) [4]
  - Generalized-LMB (GLMB) [5]
  - Classical Single-Object Filter approach with underlying track management (BuTd) [6]



## Test Scenario

- Real-world scenario in the suburbs near our university
- Passing cars as dynamic objects
- Ground truth obtained with an installed INS-sensor
- Goal: Estimate x- and y-position of our ground-truth object without id-switches
- Tested against:
  - Labeled Multi-Bernoulli Filter (LMB) [4]
  - Generalized-LMB (GLMB) [5]
  - Classical Single-Object Filter approach with underlying track management (BuTd) [6]



## Test Scenario

- Real-world scenario in the suburbs near our university
- Passing cars as dynamic objects
- Ground truth obtained with an installed INS-sensor
- Goal: Estimate x- and y-position of our ground-truth object without id-switches
- Tested against:
  - Labeled Multi-Bernoulli Filter (LMB) [4]
  - Generalized-LMB (GLMB) [5]
  - Classical Single-Object Filter approach with underlying track management (BuTd) [6]



## Test Scenario

- Real-world scenario in the suburbs near our university
- Passing cars as dynamic objects
- Ground truth obtained with an installed INS-sensor
- Goal: Estimate x- and y-position of our ground-truth object without id-switches
- Tested against:
  - Labeled Multi-Bernoulli Filter (LMB) [4]
  - Generalized-LMB (GLMB) [5]
  - Classical Single-Object Filter approach with underlying track management (BuTd) [6]




## Test Scenario

- Real-world scenario in the suburbs near our university
- Passing cars as dynamic objects
- Ground truth obtained with an installed INS-sensor
- Goal: Estimate x- and y-position of our ground-truth object without id-switches
- Tested against:
  - Labeled Multi-Bernoulli Filter (LMB) [4]
  - Generalized-LMB (GLMB) [5]
  - Classical Single-Object Filter approach with underlying track management (BuTd) [6]



## Comparing the Trajectories




Filter	RMSE	id-switches
GDPF (bbox)	0.63657	0
GDPF (grid)	0.89681	2
LMB	62.729	69
LMB (low det)	3.539	33
GLMB (low det)	2.334	5
BuTd	0.68749	31


## ID-switches and Run-time

Run-times for a mean of 193 objects:

- Grid: 58ms
- Bounding-Boxes: 34ms



## Video Footage of the Test-Drive



- 1 Motivation / Problem Description
- 2 Temporally-Dependent Dirichlet Process Mixture Model
- 3 Greedy Dirichlet Process Filter
- 4 Evaluation & Results
- 5 Summary**



## Conclusions and Future Work

- Proposed GDPF can robustly track an unknown number of targets
- Real-time capable even for a large number of targets
- Probabilistic data association can handle segmentation errors and unclustered data
- We demonstrated improved tracking results compared to popular approaches

### Possible Future work:

- Extend to classifying filter to utilize class-specific priors
- Modeling the target appearance by integrating extended object tracking



## Conclusions and Future Work

- Proposed GDPF can robustly track an unknown number of targets
- Real-time capable even for a large number of targets
- Probabilistic data association can handle segmentation errors and unclustered data
- We demonstrated improved tracking results compared to popular approaches

### Possible Future work:

- Extend to classifying filter to utilize class-specific priors
- Modeling the target appearance by integrating extended object tracking



## Conclusions and Future Work

- Proposed GDPF can robustly track an unknown number of targets
- Real-time capable even for a large number of targets
- Probabilistic data association can handle segmentation errors and unclustered data
- We demonstrated improved tracking results compared to popular approaches

### Possible Future work:

- Extend to classifying filter to utilize class-specific priors
- Modeling the target appearance by integrating extended object tracking



## Conclusions and Future Work

- Proposed GDPF can robustly track an unknown number of targets
- Real-time capable even for a large number of targets
- Probabilistic data association can handle segmentation errors and unclustered data
- We demonstrated improved tracking results compared to popular approaches

Possible Future work:

- Extend to classifying filter to utilize class-specific priors
- Modeling the target appearance by integrating extended object tracking



## Conclusions and Future Work

- Proposed GDPF can robustly track an unknown number of targets
- Real-time capable even for a large number of targets
- Probabilistic data association can handle segmentation errors and unclustered data
- We demonstrated improved tracking results compared to popular approaches

Possible Future work:

- Extend to classifying filter to utilize class-specific priors
- Modeling the target appearance by integrating extended object tracking



## Conclusions and Future Work

- Proposed GDPF can robustly track an unknown number of targets
- Real-time capable even for a large number of targets
- Probabilistic data association can handle segmentation errors and unclustered data
- We demonstrated improved tracking results compared to popular approaches

Possible Future work:

- Extend to classifying filter to utilize class-specific priors
- Modeling the target appearance by integrating extended object tracking



-  L. Wang, D. B. Dunson, B. Branch, and M. A., “Fast Bayesian Inference in Dirichlet Process Mixture Models,” *Journal of Computational and Graphical Statistics*, vol. 20, no. 1, 2011.
-  D. M. Blei and P. I. Frazier, “Distance Dependent Chinese Restaurant Processes,” *Journal of Machine Learning Research*, vol. 12, 2011.
-  S. Särkkä, *Bayesian Filtering and Smoothing*. Cambridge University Press, 2013, vol. 3.
-  S. Reuter, B.-T. Vo, B.-N. Vo, and K. Dietmayer, “The Labeled Multi-Bernoulli Filter,” *IEEE Trans. Signal Process.*, vol. 62, no. 12, Jun 2014.
-  B.-N. Vo, B.-T. Vo, and H. G. Hoang, “An Efficient Implementation of the Generalized Labeled Multi-Bernoulli Filter,” *IEEE Trans. Signal Process.*, vol. 65, no. 8, 2017.
-  M. Himmelsbach and H.-J. Wuensche, “Tracking and Classification of Arbitrary Objects with Bottom-Up/Top-Down Detection,” in *Proc. IEEE Intelligent Vehicles Symp. (IV)*. IEEE, 2012.



Thank you.

